

ELCW Series - Dry all Bead Application

Interior Joints (Wall)

FEATURES

COMPLEMENTARY SEAL COLORS A

UIC ER INSTALLATION R

DETAILS

MATERIAL

6063-T5 Aluminum, Meets ASTB B221 Santoprene

FINISH Mill

MOVEMENT

- Thermal: Horizontal

MOUNTING Flush with Drywall Bead

JOINT SIZE 1 inch to 3 inches


LENGTH 10 Linear Feet

APPLICATION Interior

INSTALLATION Floor

OPTIONS Moisture Barrier, Fire Barrier
additional materials, sizes and finishes
upon request

WALL-TO-WALL



MODELS

MODEL	APPLICATION	JOINT SIZE AT MEAN T°F	EXPOSED SIGHT LINE	TOTAL MOVEMENT
ELCW-100	Wall/Ceiling to Wall/Ceiling	1" (25mm)	1" (25mm)	.5" (13mm)
ELCW-200	Wall/Ceiling to Wall/Ceiling	2" (51mm)	2" (51mm)	1" (25mm)
ELCW-300	Wall/Ceiling to Wall/Ceiling	3" (76mm)	3" (76mm)	1.5" (38mm)
ELCW-100W	Wall/Ceiling to Corner	1" (25mm)	1" (25mm)	.5" (13mm)
ELCW-200W	Wall/Ceiling to Corner	2" (51mm)	2" (51mm)	1" (25mm)
ELCW-300W	Wall/Ceiling to Corner	3" (76mm)	3" (76mm)	1.5" (38mm)



Erie Metal Specialties, Inc.
13311 Main Road
Akron, NY 14001

Phone: 716-542-3991
Website: www.eriemetal.com
E-Mail: sales@eriemetal.com