ENWJ Series Wall System



DETAILS

MATERIAL 6063-T6 Aluminum

FINISH Clear Anodize

MOVEMENT

• Thermal: Horizontal

MOUNTING Surface

JOINT SIZE 1 inch to 3 inches

LENGTH 10 Linear Feet **APPLICATION** Interior

INSTALLATION Wall or Ceiling

OPTIONS Moisture Barrier, Fire Barrier

MODELS

MODEL	INSTALLATION	JOINT SIZE AT MEAN T°F	SYSTEM WIDTH	TOTAL MOVEMENT
ENWJ-100	Wall-to-Wall	1" (25mm)	3" (76mm)	0.5" (13mm)
ENWJ-100W	Wall-to-Ceiling/Corner	1" (25mm)	3" (76mm)	0.5" (13mm)
ENWJ-150	Wall-to-Wall	1.5" (38mm)	4" (102mm)	2" (51mm)
ENWJ-200	Wall-to-Wall	2" (51mm)	5.75" (146mm)	2" (51mm)
	Wall-to-Ceiling/Corner	, ,	, ,	,
	Wall-to-Wall	- (- /	7" (178mm)	- (- /
ENWJ-300W	Wall-to-Ceiling/Corner	3" (76mm)	7" (178mm)	3" (76mm)

Phone: 716-542-3991


Website: www.eriemetal.com E-Mail: sales@eriemetal.com Aluminum Wall and Ceiling system is capable of thermal movement. It mounts easily after final wall surface is complete. Standard with a clear anodize finish.

FEATURES

COORDINATING CORNERS Available with corner option for a complete solution.

ARCHITECTURAL AESTHETICS The sliding cover plate with a clear anodized finish provides a highend appearance.

CONTINUOUS SIGHT LINE This system can be used on walls, ceilings and corners to provide seamless and continuous aesthetics.



Wall-to-Wall

