


Factory Applied Dow 790 Or Pecora 890 Silicone



CSS(DS)-SERIES
Vertical Condition

* Note: Epoxy only used for sizes 6" and greater.
* Sizes available in 0.25" increments and up to 9".
Contact EMS for additional information.

SEAL COLOR:	
DOW 790:	_____
PECORA 890:	_____
SPECTRUM 1:	_____

WALL-WALL/CORNER APPLICATION

MOVEMENT: +/- 50% NOMINAL JOINT WIDTH
STOCK LENGTHS: 5'-0"

PRODUCT	"A" Min. Width IN (MM)	"A" Mid Range IN (MM)	"A" Max. Width IN (MM)	Total Movement IN (MM)	Seal Depth IN (MM)
CSS(DS)-050	0.25" (6.4)	0.50" (12.7)	0.75" (19.1)	0.50" (12.7)	1.50" (38.1)
CSS(DS)-100	0.50" (12.7)	1.00" (25.4)	1.50" (38.1)	1.00" (25.4)	1.50" (38.1)
CSS(DS)-150	0.75" (19.1)	1.50" (38.1)	2.25" (57.2)	1.50" (38.1)	2.00" (50.8)
CSS(DS)-200	1.00" (25.4)	2.00" (50.8)	3.00" (76.2)	2.00" (50.8)	2.00" (50.8)
CSS(DS)-250	1.25" (31.8)	2.50" (63.5)	3.75" (95.3)	2.50" (63.5)	2.00" (50.8)
CSS(DS)-300	1.50" (38.1)	3.00" (76.2)	4.50" (114.3)	3.00" (76.2)	3.00" (76.2)

NO.	Description	Date	By
<small>The information contained herein is the proprietary property of ERIE METAL SPECIALTIES, INC. No portion of it may be reproduced by any means or used in any form except for the purpose for which it was intended. All rights of design and invention are hereby reserved.</small>			



13311 Main Road * Akron * New York * 14001
Phone: (716) 542-3991 * Fax: (716) 542-3996 * E-mail: sales@eriemetal.com

PROJECT: N/A
TITLE: CSS(DS)-Series Vertical Condition

Detailed by: BAF	Date: 07/20/16
Checked by: SLP	Date: 07/22/16
Scale: NTS	EMS Job #: N/A
Sheet No.: 1 of 1	Drawing No.: CSS(DS)-1